



aegex10™ intrinsically safe tablet

Aegex Technologies provides intrinsically safe solutions for the world's most hazardous industrial operations in oil and gas, chemical, mining, pharmaceutical, public safety, utilities and other industries with explosive environments. Aegex solutions bring real-time connectivity to hazardous areas, helping organizations harness the power of data to optimize efficiency, safety and productivity.



Oil & Gas



Chemical



Mining



Pharmaceutical



Public Safety



Utilities

The **aegex10™ Intrinsically Safe Tablet** is the most advanced, efficient, lightweight and rugged Windows tablet that is purpose-built for **Zone 1 / Division 1 hazardous areas**. Simple to deploy, it is the basis for an Industrial Internet of Things platform for hazardous industries, allowing operations to easily begin their digital transformation to Industry 4.0.

- Purpose-Built Intrinsically Safe and Enterprise-Class Tablets:**
 Aegex devices are certified ATEX/IECEX Zone 1; certified by SGS to UL 913 Class I, II, III Division 1 Groups A-G; and IP65 for hazardous (classified) locations.
- Solutions for All Hazardous Zones and Jobs:**
 Aegex devices run the operating system and applications that allows for secure enterprise deployments.
- Enterprise Collaboration**
 Aegex devices use 4G LTE or Wi-Fi for real-time communications.



Certified ATEX/IECEX Zone 1

Certified by SGS to
UL 913 C I, II, III Div 1

10.1" WUXGA Display

Powered by Intel
Atom Quad Core

Windows 10



Registered Address

ABLE Instruments & Controls Ltd
Cutbush Park, Danehill, Lower Earley,
Reading, Berkshire, RG6 4UT. UK.

Phone

+44 (0)118 9311188

Email


info@able.co.uk

Web

able.co.uk

E-commerce

247able.com



Registered in England No. 01851002. VAT No. GB 417 2481 61



SPECIFICATIONS

Intrinsically Safe Certifications	<p>UL913 5th edition: C I, II, III Div 1 Gr A-G T4, T_{amb} = -10°C...+50°C Cl Z0 Gr IIC T4 IP65, T_{amb} = -10°C...+50°C CAN/CSA-22.2 Part 157</p> <p>IECEX 60079-0 & -11: Ex ib IIC T6 Gb, T_{amb} = -10°C...+50°C Ex ib IIIC T85°C Db IP6X, T_{amb} = -10°C...+50°C Ex ib I Mb, Tamb = -10°C...+50°C</p> <p>ATEX 60079-0 & -11: Ⓜ II 2G Ex ib IIC T6 Gb, T_{amb} = -10°C...+50°C Ⓜ II 2D Ex ib IIIC T85°C Db IP6X, T_{amb} = -10°C...+50°C Ⓜ I M2 Ex ib I Mb, Tamb = -10°C...+50°C</p>
Exterior	<p>Dimensions: 273 x 185 x 16.8 mm (10.75 x 7.28 x 0.66 in) Weight: 980 grams (2.16 lbs) IP65</p>
Display	<p>Screen: 10.1" AHVA Full HD Plus Resolution: 1920 x 1200 Capacitive touch: Multi-touch Contrast 800:1 Viewing angle (up/down, left/right) 170°</p>
Battery Life	Up to 12 hours of web browsing (Battery: 3.8V, 8700mAh, 33Wh)
Charging time (in standby)	<p>Docking station: 0-90% in 2.5hours, to 100% in approx. 3.5 hours USB charger: 0-90% in 4hours, to 100% in approx. 5.5 hours</p>
Storage/RAM	128GB storage / 4GB RAM
CPU Standard	<p>Intel® Quad-Core Atom processor 2.39GHz* Wi-Fi 802.11 a/b/g/n dual band Bluetooth® 4.0 Low Energy technology NFC Intel Wireless Display</p>
LTE Options (Standard +)	<p>LTE (North America): Sierra EM7355 - LTE: FDD Band 2,4,5,13,17,25 all bands with diversity - UMTS/HSPA+ Band 1,2,4,5,8, all bands with diversity - CDMA 1xRTT/EV-DO Rev A: BC0, BC1, BC10 - GSM/GPRS/EDGE: Quad-Band</p> <p>* LTE (EU, US, AU): Telit LN940A9 - LTE: Band 1, 2, 3, 4, 5, 7, 8, 12, 13, 17, 18, 19, 20, 21, 25, 26, 28, 29, 30, 38, 39, 40, 41, 66 - WCDMA: Band 1, 2, 3, 4, 5, 6, 8, 19 - GSM/GPRS/EDGE: N/A</p> <p>LTE (international): Huawei ME936 - LTE: FDD Band 1,2,3,4,5,7,8,13,17,20, all bands with diversity - WCDMA/HSD-PA/HSU-PA/HSPA+: Band 1,2,4,5,8, all bands (NOTE: Last day to order Huawei is December 15, 2020).</p>
Location	GPS / GLONASS (cold start <30s, warm start < 5s)
Ports	<p>Full-size USB 2.0 USB 3.0, Ethernet, and HDMI on system connector Micro USB for charging Charging pads (12V) microSDXC™ card slot (supports up to 2TB) Headset jack</p>
Software	Windows 10 IoT Enterprise
Cameras, Video & Audio	<p>8.0 megapixel autofocus rear-facing camera with flash, full HD video 2.0 megapixel front-facing camera full HD video Front and rear microphones Stereo speakers</p>
Sensors	Ambient light sensor, Accelerometer, Gyroscope, E-Compass, SAR proximity sensor
Security	<p>Silicon Level, Intel Security (SMEP, PDRNG, fTPM, and TPM 2.0) Software Level Device Control BitLocker</p>
In the box	aegex10™ intrinsically safe tablet Wall charger (power supply + USB cable)



*Base Frequency 1.59 GHz, Burst Frequency 2.39 GHz

*Subject to verification of local carrier requirements

**P2P: ISO 18092, Reader/Writer: ISO 14443 –A-B, MIFARE, FelCa®, ISO 15693, NFC Forum Tag Types 1 to 4
 Card emulation: ISO 14443 –A-B-B', MIFARE, FelCa RF, Distance up to 3 cm

Registered Address

ABLE Instruments & Controls Ltd
 Cutbush Park, Danehill, Lower Earley,
 Reading, Berkshire, RG6 4UT. UK.

Phone

+44 (0)118 9311188

Email


info@able.co.uk

Web

able.co.uk

E-commerce

247able.com



Registered in England No. 01851002. VAT No. GB 417 2481 61