

Data Sheet

BA324SG


2-wire 4/20mA 5 digit indicator



Supplied by

247able.com

Call us on +44 (0)118 916 9420 | Email info@247able.com



The **BA324SG loop powered 4/20mA** indicator is a new low cost alternative to a flameproof Ex d indicator featuring a large 29mm high display. Increased safety Ex eb and dust ignition protection by enclosure Ex tb certification allow it to be safely installed in Zones 1, 2, 21 or 22 without the need for a Zener barrier or a galvanic isolator. Installation requirements are the same as those for an Ex d instrument.

Main application of the BA324SG is to display a measured variable or control signal in engineering units within a hazardous area. The indicator may be connected in series with almost any Zone 1 or 2 hazardous area 4/20mA loop containing flameproof Ex d, pressurised Ex p or increased safety Ex e instrumentation. The BA324SG may also be used as an alternative for an Ex nA indicator in Zone 2.

Dust ignition protection by enclosure Ex tb certification confirms that the BA324SG may be safely installed in a Zone 21 or 22 dust atmosphere. Again there is no need for a Zener barrier or galvanic isolator.

IECEx and ATEX certification permits the BA324SG indicator to be installed worldwide. Application Guide AG320 describes the indicator's multiple explosion protection and includes examples of how it may be used.

The large 29mm high 5 digit display and 31 segment bargraph provides maximum contrast and has a very wide viewing angle, allowing the BA324SG indicator to be easily read in most lighting conditions. An optional factory fitted backlight is available for installations in poorly illuminated areas. The five digits,

with four decimal points and a negative sign, may be configured to display any variable between -99999 and 99999.

IP66 and impact protection is provided by the robust GRP enclosure, which has an 8mm thick armoured glass window and a silicone gasket. The BA324SG is surface mounting but can be pipe or panel mounted using an accessory kit.

Display zero and span are independently adjustable allowing the indicator to be calibrated to display any linear variable represented by the 4/20mA signal. Non-linear variables such as flow and tank level may be displayed in linear engineering units using the instruments root extractor and adjustable sixteen segment lineariser. For weighing applications a tare function is included.

Display backlighting which is powered by the 4/20mA loop is available as a factory fitted option. It provides green background illumination which enhances daylight viewing and enables the display to be read at night or in poorly illuminated areas.

The scale card showing the units of measurement and tag information slides into an internal slot and can easily be changed on-site. New instruments can be supplied with the scale card printed to show customer specified information for no additional charge. If this is not requested, a blank card is fitted to which a legend can easily be added on-site.

Reliability is ensured by protection from incorrect connection and radio frequency interference. The indicator has been subjected to extensive vibration and thermal testing and is supported by a three year guarantee.

BA324SG

2-wire 4/20mA

5 digit indicator

Lower cost alternative for Ex d flameproof indicator.

Ex eb increased safety & Ex tb certification allows installation in Zones 1, 2, 21 or 22.

- ◆ 4/20mA loop powered
- ◆ 5 digit 29mm high display & 31 segment bargraph.
- ◆ IECEx and ATEX Ex eb gas and Ex tb dust certification.
- ◆ May be connected in series with an Ex d, Ex e, Ex p, Ex nA, Ex m or Ex t loop without a Zener barrier or isolator.
- ◆ Push buttons usable in hazardous area.
- ◆ IP66 impact resistant GRP enclosure.
- ◆ Root extractor, 16 segment lineariser and tare function.
- ◆ Optional loop powered backlight.
- ◆ 3 year guarantee

www.beka.co.uk/ba324sg



BEKA


associates

BEKA associates Ltd. Old Charlton Rd.
Hitchin, Hertfordshire, SG5 2DA, U.K.
Tel. (01462) 438301 Fax (01462) 453971
e-mail sales@beka.co.uk www.beka.co.uk


SPECIFICATION

Input	
Current	4 to 20mA HART @ transparent
Voltage drop at 20°C	Less than 5.3V
Overrange	Less than 9.1V with optional backlight ±40V will not damage the indicator.
Display	
Type	Liquid crystal, 5 digits 29mm high non-multiplexed.
Span	Adjustable between 0 & ±99999 for a 4/20mA input
Zero	Adjustable between 0 & ±99999 with 4mA input
Decimal point	1 of 4 positions or absent
Polarity	Automatic minus sign
Zero blanking	Blanked apart from 0 in front of the decimal point.
Direction	Display may increase or decrease with increasing 4/20mA input.
Reading rate	2 per second
Bargraph	31 segments 80mm long
Overrange	99999 or -99999 with all decimal points flashing
Push buttons	
	(Function in display mode)
▼	Shows display with 4mA input
▲	Shows display with 20mA input
P	Displays input in mA or as a % of span.
E	Used for tare function
Accuracy at 20°C	
Linear	±0.02% of span ±1digit
Root extracting	±16µA at input ±1 digit.
Temperature effect on:	
Zero	Less than 25ppm of span/°C
Span	Less than 50ppm of span/°C
Series mode rejection	Less than 0.05% of span error for 1mA pk to pk 50 or 60Hz interference.
Safety certification	
	(Both certificates specify types of protection in alphabetical order. Zener barriers or galvanic isolators are not required.)
International IECEx	
Code	Ex eb ib mb IIC T5 Gb <i>Increased safety Ex eb</i>
	Ex ib mb tb T80°C Db <i>Protection by enclosure Ex tb.</i>
Rated voltage U _N	30V dc
Cert. No.	IECEx ITS 19.0018X
Europe ATEX	
Code	II 2G Ex eb ib mb IIC T5 Gb <i>Increased safety Ex eb.</i>
	II 2D Ex ib mb tb T80°C Db <i>Protection by enclosure Ex tb.</i>
Rated voltage U _N	30V dc
Cert. No.	ITS19ATEX304891X
Environmental	
Operating temp	-40 to +60°C
Storage temp	-40 to +85°C
Humidity	To 95% at 40°C non-condensing
EMC	Complies with EMC Directive 2014/30/EU
Mechanical	
Enclosure	
Material	GRP (Glass reinforced polyester)
Ingress protection	IP66
Impact protection	Enclosure 7J, Window 4J
Weight	1.2kg
Terminals	Spring clamp for a single 0.2 to 1.5mm ² solid wire. or 0.2 to 2.5mm ² stranded wire
Scale card	Slide-in card visible through display window. Printed with customer specified units of measurement, tag information and company logo for no additional charge. #

DIMENSIONS (mm)



TERMINAL CONNECTIONS



Accessories

Backlight	
Colour	Green
Input voltage drop	9.1V at 20mA
Legend plate	316 stainless steel plate laser engraved with tag number or application information #
Pipe mounting kit BA393G	316 stainless steel #
Panel mounting kit BA394G	Mounts indicator into an open panel aperture. Does not seal aperture between the front and the rear of the panel. #

See accessory datasheet for details

HOW TO ORDER

Model number	Please specify BA324SG
Display mode	Linear, root or lineariser*
Display at:	
4.000mA	XXXXX
20.000mA	XXXXX
Scale card marking	
Units	Legend required
Tag	Legend required
Logo	If required
Accessories Please specify if required	
Display backlight	Backlight
Stainless legend plate	Legend required
Pipe mounting kit	BA393G
Panel mounting kit	BA394G

* Will be set to display 0.00 at 4mA and 100.00 at 20mA with a linear display if calibration information is not supplied. Can easily be recalibrated on-site.