

Data Sheet

# ISAFE MOBILE

IS530.2



Supplied by

**247cable.com**

Call us on +44 (0)118 916 9420 | Email [info@247able.com](mailto:info@247able.com)



**ZONE 2/22  
CL I, II, III DIV 2**



**13-pin ISM interface**



**Android™ 13**

**Zero-touch capable  
MDM compatible**

**IS530.2**



The high-performance industrial smartphone can be used in a multifunctional way thanks to the ISM interface. Additional modules such as an RSM, PTT headsets or the professional IS-TH1 barcode scanner make the IS530.2 a high-performance multifunctional device. The smartphone is Android Enterprise Recommended, zero-touch capable and MDM compatible.

› Android is a trademark of Google LLC. All trademarks and copyrights are the properties of their respective owners. › © 2023 by i.safe MOBILE GmbH | All rights reserved. | Misprints, errors and modifications excepted. | 1035MD01REV11\_EN\_01.2024



< IS530.2 >



ATEX approval: EX-Zone 2/22  
Ⓜ II 3G Ex ic IIC T4 Gc IP64  
Ⓜ II 3D Ex ic IIIC T135°C Dc IP64



IECEx approval: EX-Zone 2/22  
Ex ic IIC T4 Gc IP64  
Ex ic IIIC T135°C Dc IP64



NEC500 approval:  
Class I, II, III Division 2  
Groups A B C D F G T4



EAC approval:  
2Ex ic IIC T4 Gc X  
Ex ic IIIC T135°C Dc X

Further approvals: PCEC (China)

## TECHNICAL FEATURES

<b>Operating system</b>	Android™ 13
<b>Processor</b>	SDM660 Octa-Core (Kryo Gold-Quad cores 2,2 GHz; Kryo Silver-Quad cores 1,8 GHz)
<b>Memory</b>	4 GB RAM   64 GB internal memory   microSD memory up to 128 GB
<b>Frequencies</b>	2G GSM: 850/900/1800/1900 MHz 3G WCDMA: UMTS B1/2/4/5/8 4G LTE-FDD: B1/2/3/4/5/7/8/12 with MFB1 B13/14/17/20/25/26/28A/28B/29/30/66 4G LTE-TDD: B38/B39/B40/B41 4G LTE-SCDMA: B34/B39
<b>Dimensions</b>	size: 155 x 80 x 25 mm   weight: 325 g
<b>Display</b>	4,5" Gorilla Glass® 3. generation   854 x 480 pixels
<b>Battery</b>	3600 mAh, 3,8 V, 13,68 Wh   replaceable
<b>Camera</b>	13 MP AF rear camera   5 MP FF front camera
<b>Connections</b>	WiFi 2,4 GHz + 5 GHz: IEEE 802.11 a/b/g/n/ac/e/k/r/h with max. 8 connections hotspot Bluetooth® 5 GPS, A-GPS, Glonass, Beidou, Galileo Near Field Communication
<b>Types of protection</b>	IP68 dust-/waterproof   MIL-STD-810G   usable from -20 °C to +60 °C

## FURTHER FEATURES



SOS key for loneworker protection  
LWP ready (third party application required,  
based on country specific regulations)



13-pin ISM interface for a quick and safe  
connection of additional devices for a  
wide range of applications



Dual micro-SIM



Amplified loudspeaker



Magnetic charger port



Accelerometer, gyroscope, light, magnetic,  
proximity, pressure sensors

## SET CONTENT

Smartphone, Battery, Type C USB Cable, Magnetic Charger Cable, Power Adapter universal, Screwdriver, Display Protection Foil, Quick Start Manual and Safety Instructions

Please visit our website and you will find more detailed information, as well as an overview of compatible accessories.