

Quick Selection Guide for UE Products

PRODUCT SERIES Click on product to view full specifications and datasheet online →	J6	10	12	J21K	24	J40	54	55	100	117	120	400	800	820E/822E	One Series					Excela	Vanguard	
															1XSWLL	1XSWHL 1XSWHH	1XTXSW	1XTX00	ONE Safety (25LP)			
VARIABLE																						
Pressure	●	●	●			●	●		●	●	●	●			●	●	●	●	●	●	●	
Vacuum	●		●	●		●	●		●	●	●	●			●	●	●	●	●	●	●	
Differential Pressure			●	●	●				●	●	●	●			●	●	●	●	●	●	●	
Temperature			●				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Gas																						●
ENCLOSURE																						
Open frame						●	●	●														
Enclosure Type 1 Gen. Purpose		●		●	●		●						●									
Enclosure Type 4 Watertight		●											○	●								
Enclosure Type 4X Watertight	●		●	○				●	●	●	●	●			●	●	●	●	●	●	●	●
Zone 0, Intrinsically Safe	○	○	○	○					○	○	○	○			●							
Division 1 Zone 1, Hazardous Location, IP 66 Rating			●								●			●	●	●	●	●	●	●	●	●
Division 2 Zone 2, Hazardous Location, IP 65 Rating			●							●	●			●	●	●	●	●	●	●	●	●
OUTPUT																						
Single Switch SPDT	●	●		●	●	●	●	●	●		●	●	●	●	SPST	SPST				SPST	●	
Dual Switch SPDT							●	●			●	●	●	●			2xSPST					
Triple Switch SPDT												●										
DPDT									○		○	○										
Dual Switch DPDT												○										
Adjustable Deadband	○			○		○	○		○		○	○			●	●	●			●	●	
Hermetically-Sealed Switch SPDT			●							●	○											
Hermetically-Sealed Switch DPDT			●							○	○											
4 to 20 mA, HART																	●		●			
Wireless HART																						●
SENSORS																						
Welded Stainless Steel Diaphragm			●						●	●	●	●			●	●	●	●	●	●	●	●
Stainless Steel Bellows	●			●		●			●	●	●	●										
Elastomer Diaphragm		●	●		●		●		●	●	●	●										
Brass/Bronze Bellows	●			●		●			●	●	●	●										
Piston	●	●	●			●			●		●	●										
Process Alloy				○					○	○	○											
Local Temperature Mount			●				●		●	●	●				●	●	●	●	●	●	●	●
Remote Temp. Mount			●				●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Toxic (H ₂ S, CO, NH ₃)																						●
Combustible (CH ₄ , C ₃ H ₈ , LEL%)																						●
MISCELLANEOUS																						
Terminal Block					●					●	●		○	●	●	●	●	●	●	●	●	●
Visual Indication*					○			○	○		○	○	●	●	●	●	●	●	●	●	●	●
Dual Seal Certified			●												○	○	○	○	○	○	○	○
SIL 2 Certified			○						○		○				●	●				●		
Battery Operated																						●

*Visual indication may be through a pilot light option or display of process pressure or temperature readings.

● Available ○ Option

Registered Address

ABLE Instruments & Controls Ltd
Cutbush Park, Danehill, Lower Earley,
Reading, Berkshire, RG6 4UT. UK.

Phone

+44 (0)118 9311188

Email

info@able.co.uk

Web

able.co.uk

E-commerce

247able.com



Certification Guide* for UE Products

CERTS / APPROVALS	J6	10	12	J21K	24	J40	54	55	100	117	120	400	800	820/822E	One Series				Excela	Vanguard		
															1XSWLL	1XSWHL 1XSWHH 1XTXSW & 1XTX00	ONE Safety (25LP)	Excelsa		TCD50	TCD60	
NORTH AMERICA																						
	FM																					
	UL Mark	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
	CL I, Grp A			●																		
	CL I, Grp B										●				●							
	Intertek Ex db ia [ia] IIB T4 Gb IP66																				●	
	Intertek Ex db ia [ia] IIC																					●
	CRN	●	●	●	●	●	●		●	●	●	●					●	●	●			
Enclosure Rating			Type 4	4X						4X	4X	4X					4X	4X	4X	4X	4X	4X
EUROPE																						
	ATEX Ex ia	●	●	●	●					●	●	●	●				●				●	●
	ATEX Ex nA																●	●				
	ATEX Ex db				●							●				●	●	●	●		●	●
	ATEX Ex tb				●							●				●	●	●	●			
Electromagnetic Compatibility (EMC)	2014/30/EU																●	●	●			
Low Voltage Directive (LVD)	2014/35/EU	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		●	●
Pressure Equipment Directive (PED)	2014/68/EU	●	●	●	●	●	●		●	●	●	●					●	●	●			
Enclosure Rating				IP66							IP66			IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66
INTERNATIONAL																						
	IEC Ex ia	●	●	●	●					●	●	●	●				●				●	●
	IEC Ex nA																●	●				
	IEC Ex db				●							●				●	●	●	●		●	●
	IEC Ex tb				●							●				●	●		●			
Enclosure Rating				IP66							IP66			IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66	IP66
SIL																						
	SIL			●					●	●						●			●			

Ex d = Flame-Proof
 Ex tb = Dust Protected
 Ex ia = Intrinsic Safety
 Ex nA = Non-Arcing
 Ex tb = Dust Protected

CL 1, Groups A - Class 1, Groups A, B, C, D; Class II, Groups E, F, G: Class III
 CL I, Groups B = Class 1, Groups B,C,D; Class II, Groups E, F, G: Class III
 ● Available ○ Option

UE is a registered trademark of United Electric Controls Company.
 Excela, Vanguard and The Sensor Box are trademarks of United Electric Controls Company.

The following registered trademarks are property of the respective companies:
 Lexan General Electric Co.
 HART and WirelessHart FieldComm Group

Certification Guide* for UE Products

CERTS / APPROVALS	J6	10	12	J21K	24	J40	54	55	100	117	120	400	800	820/822E	One Series				Excela	Vanguard
															1XSWLL	1XSWHL XSWHH 1XTXSW & 1XTX00	ONE Safety (25LP)			
BRAZIL																				
	INMETRO Ex ia			○					○	○	○	○			○					
	INMETRO Ex nA														○					
	INMETRO Ex db			○							○				○	○	○	○		
	INMETRO Ex tb			○							○				○	○	○	○		
CHINA																				
	CCC / Ex ia	○	○	○	○				○	○	○	○			○					
	CCC / Ex ec														○	○				
	CCC / Ex db			○							○		○		○	○	○	○		
	CCC / Ex tb			○							○		○		○	○	○	○		
INDIA																				
	PESO Ex d			△							△			△	△	△	△			●
	PESO Ex ia	△	△	△	△				△	△	△	△			△					●
KOREA																				
	KOSHA/KGS Ex d			○							○			○	○	○				○
	KOSHA/KGS Ex tb										○									
	KOSHA/KGS Ex ia														○					○
RUSSIA, KAZAKHSTAN, BELARUS, ARMENIA, KYRGYZSTAN																				
	EAC Ex db			●							●			●	●	●	●	●		●
	EAC Ex tb			●							●			●	●	●	●	●		●
	EAC Ex ia	●	●	●	●				●	●	●	●			●					
TAIWAN																				
	ITRI										●				●	●				
UKRAINE																				
	UkrEx			●							●			●						
UNITED ARAB EMIRATES (UAE)																				
	ECAS / Ex ia	△	△	△	△				△	△	△	△			△					
	ECAS / Ex db			△							△		△		△	△	△	△		
	ECAS / Ex tD			△							△		△		△	△	△	△		
	ECAS / Ex nA														△	△				

Ex d = Flame-Proof
 Ex tb = Dust Protected
 Ex ia = Intrinsic Safety
 Ex nA = Non-Arcing
 Ex tb = Dust Protected

CL 1, Groups A - Class 1, Groups A, B, C, D; Class II, Groups E, F, G: Class III
 CL I, Groups B = Class 1, Groups B,C,D; Class II, Groups E, F, G; Class III

● Available ○ Option △ Contact ABLE

Registered Address

ABLE Instruments & Controls Ltd
 Cutbush Park, Danehill, Lower Earley,
 Reading, Berkshire, RG6 4UT. UK.

Phone

+44 (0)118 9311188

Email

info@able.co.uk

Web

able.co.uk

E-commerce

247able.com

